

PRODUCT DATASHEET LED PERFORMANCE STICK 9 W/4000 K B22d

LED PERFORMANCE STICK | LED lamps, classic stick shape



Areas of application

- Suitable for indoor applications.
- $\,$ Replacement for conventional compact fluorescent lamps with wattage 11 W, 15 W and 24 W

Product benefits

- Creation of the preferred light ambience thanks to dimming
- Wide beam angle: 200°
- Instant 100 % light, no warm-up time
- Stylish and modern design
- No UV and near-IR radiation in the light beam
- Reliable operation thanks to brand quality

Product features

- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Long lifetime up to 25,000 h
- Mercury-free lamps
- Input voltage: 220...240 V_{AC}
- Storage temperature from -20 °C to up to +80 °C, up to 95 % relative humidity



B22d

– Operating temperature from -20 $^{\circ}\text{C}$ to up to +35 $^{\circ}\text{C}$, up to 95 % relative humidity

TECHNICAL DATA

Electrical data

Nominal wattage	9 W
Construction wattage	9.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	60 W
Nominal current	58 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor λ	0.70

Photometrical data

Luminous flux	800 lm
Luminous efficacy	88 lm/W
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840
Standard deviation of color matching	≤6 sdcm

Light technical data

Beam angle	200 °
Starting time	0.5 s

Dimensions & Weight

Overall length	116.00 mm
Diameter	41.00 mm
Maximum diameter	41 mm
Product weight	28.00 g

Temperatures & operating conditions

Ambient temperature range	-20+30 °C
---------------------------	-----------

Lifespan

Number of switching cycles	100000
----------------------------	--------

Additional product data

Base (standard designation)	B22d
Mercury content	0.0 mg

Capabilities

Certificates & Standards

Country-specific categorizations

Order reference	LP STICK DIM 9W

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	B22d
Length	116.00 mm
Height	41.00 mm
Width	41.00 mm

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075636163	Folding box 1	42 mm x 42 mm x 117 mm	42.00 g	0.21 dm ³
4099854275715	Shipping box 10	218 mm x 93 mm x 134 mm	480.00 g	2.72 dm ³
4058075636170	Shipping box 10	218 mm x 92 mm x 132 mm	491.00 g	2.65 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.