

# PRODUCT DATASHEET CLAS A FR 60 W 230 V E27

CLASSIC A | Incandescent lamps, classic bulb shape



#### Areas of application

- Domestic applications
- Shops, hotels and restaurants
- Meeting rooms
- Shopping centers
- Luminaires with E27 or B22d holders (screw or bajonet holders)

#### **Product benefits**

- Brilliant light (CL clear version)
- Reduced glare and softened shadows (FR frosted version)

#### Product features

- Non-oxidizing aluminum base

## TECHNICAL DATA

#### Electrical data

Nominal wattage	60 W
Construction wattage	60.00 W
Nominal voltage	230 V
Nominal current	260 mA

## Photometrical data

Luminous flux	710 lm
Luminous efficacy	11 lm/W
Color temperature	2700 K
Light color	27

# Light technical data

Starting time	0 s

## Dimensions & Weight

Overall length	100.00 mm
Diameter	55,0 mm
Product weight	27.3 g

## Additional product data

Base (standard designation)	E27	
Mercury content	0.0 mg	
Mercury-free	Yes	
Design / version Frosted		
Product remark	Banned from 1.9.2009 as per EU phase-out plan	

# Capabilities

## Country-specific categorizations

ILCOS	IAA/F-60-230-E27-60
Order reference	CLAS A FR 60W 2

# Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Length	100.00 mm
Height	55,0 mm
Width	55,0 mm

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300005485	Folding box 1	97 mm x 56 mm x 56 mm	35.75 g	0.30 dm <sup>3</sup>
4050300009193	Bundle 10	147 mm x 97 mm x 248 mm	357.50 g	3.54 dm <sup>3</sup>
4050300200477	Shipping box 100	570 mm x 207 mm x 294 mm	3945.00 g	34.69 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.