

# PRODUCT DATASHEET LED Value Slim Downlight 18 W/6500 K

LED VALUE SLIM DOWNLIGHT | Flat downlight luminaires



# Areas of application

- Corridors, entrance areas
- Foyers
- Elevators
- Retail

# Product benefits

- Die-cast aluminum housing for improved heat dissipation
- No light can escape at the back of the luminaires thanks a special cover
- Elegant design

### Product features

- Product color: white
- $-\,$  Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Color rendering index  $R_a$ : > 80
- High color consistency: ≤ 6 SDCM
- Luminaire efficacy: up to 89 lm/W
- Type of protection: IP20
- Lifetime (L70/B50): up to 30,000 h
- Protection class: II
- Uniform illumination



# **TECHNICAL DATA**

# Electrical data

Nominal wattage	18.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Power factor $\lambda$	0.50
Protection class	Ш

# Photometrical data

Luminous flux	1600 lm
Luminous efficacy	89 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Color rendering index Ra	80
Standard deviation of color matching	≤6 sdcm
Beam angle	120°

# Dimensions & Weight

Length	225.00 mm
Width	225.00 mm
Height	20.00 mm
Product weight	400.00 g

LDVAL SLIM downlight SQ 205 18W

# Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum

Cover material	Plastic
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-10+50 °C
Temperature range at storage	-20+70 °C
Type of protection	IP20
Dimmable	No
Mounting type	Recessed
Mounting location	Ceiling
Application environment	Indoor
Mounting length	205,0 mm
Mounting width	205,0 mm
Replaceable light source	No

# Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	25000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

# DOWNLOAD DATA

Photometric and lighting design files	Document name	
IES file (IES)	LDVAL SLIMDL SQ 205 18W 865	

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075314214	Folding box 1	265 mm x 47 mm x 230 mm	527.00 g	2.86 dm <sup>3</sup>
4058075314221	Shipping box 20	478 mm x 276 mm x 482 mm	11307.00 g	63.59 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.