

# PRODUCT DATASHEET LED ECO Downlight 10.00 W 3000 K GEN1

LED ECO DOWNLIGHT | Spotlights and downlights



# Areas of application

- Corridors, entrances, foyers, stairwells, elevators

#### Product benefits

- Low flicker light thanks to special electronic control gear
- Photobiological safety according to IEC 62471, risk group RG0

#### **Product features**

- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Long lifetime (L70/B50): up to 15,000 h
- Color rendering index R<sub>a</sub>: ≥ 80
- Direct connection to AC power supply
- Mercury-free and RoHS compliant



# TECHNICAL DATA

## Electrical data

Nominal wattage	10.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	75.000 mA
Power factor $\lambda$	0.50
Protection class	II
Operating mode	Integrated LED driver

#### Photometrical data

Luminous flux	700 lm
Luminous efficacy	70 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥80
Standard deviation of color matching	6 sdcm
Beam angle	110°

# Dimensions & Weight

Diameter	112.00 mm
Height	50.00 mm
Product weight	68.00 g



LDECO DL40 10W G1

# Materials & Colors

Product color	White
Housing color	White
Body material	Plastic
Cover material	Polycarbonate (PC)

Mercury content	0.0 mg
Application & Mounting	
Ambient temperature range	-20+40 °C
Temperature range at storage	-20+70 °C
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
Mounting diameter	95.0105.0 mm
Mounting depth	100 mm
Replaceable light source	No
Lifespan	
Lifespan L70/B50 at 25 °C	15000 h <sup>1)</sup>

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

#### **DOWNLOAD DATA**

Number of switching cycles

Photometric and lighting design files	Document name	
IES file (IES)	LDECO DL40 10W 830 G1	

15000

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075341753	Folding box	113 mm x 56 mm x 113 mm	102.00 g	0.72 dm <sup>3</sup>
4058075341760	Shipping box 30	355 mm x 300 mm x 245 mm	3734.00 g	26.09 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.